

ROOF OR ABOVE FLOOR

6" PVC COUPLING P-9087

TYPICAL I BEAM

6" PVC TUBING P-9204

36" OR 48" STANDARD BEND P-9040

FALSE CEILING

TYPE I STATION A-6000


5 FT TO FLOOR TYPICAL

CARRIERS:
6"x12" - A-9018
6"x16" - A-9019

6" ND-HUB COUPLING P-9093

TYPE II STATION A-6200

- NOTES:
1. PLUGS ARE NOT SUITABLE AS A DISCONNECT. USER MUST SUPPLY A SUITABLE DISCONNECT.
 2. 120 VAC 20 AMP. BRANCH CIRCUIT PROTECTION MUST BE PROVIDED ON EACH PLUG OUTLET BY OTHERS DURING FIELD INSTALLATION.

TOLERANCES ±1/32" FRACTIONAL DIMENSIONS TOLERANCES ±.005" DECIMAL DIMENSIONS UNLESS OTHERWISE SPECIFIED	MATERIAL: ---	 <p>EAGLE PNEUMATIC, INC. (863)644-4870</p>
INFORMATION CONTAINED HEREIN IS PROPRIETARY TO EAGLE PNEUMATIC, INC. ALL RIGHTS RESERVED	FINISH: ---	
TITLE: SYSTEM, BASIC 6 INCH PRESSURE - PRESSURE INSTALLATION	REV. 1-30/99 E-30/07/03	DRAWING NO. S-10788
	DRAWN: JAC CADFILE: A27	DATE: 1/25/00
		APPROVED: ISSUE 2