



INFORMATION CONTAINED HEREIN IS PROPRIETARY TO EAGLE PNEUMATIC, INC ALL RIGHTS RESERVED.

TOLERANCES:  
UNLESS OTHERWISE SPECIFIED  
FRACTIONS +/-1/32"  
DECIMALS +/-0.005"

REVISIONS:  
ISSUE 1 06/17/15  
ISSUE 2 02/15/16

DRAWN BY: DTS

DATE: 11/16/10

NAME:  
WIRING DIAGRAM  
3&4 INCH CASH LINE  
M2 PCB

PART NO.

E-12616

CADFILE: A20

TO SECURE GROUNDING LUGS TO FRAME USE EXTERNAL STAR WASHER BETWEEN LUG AND FRAME AND SECURE WITH #8 SHEET METAL SCREW. USE UL LISTED GROUND LUG (x2).

POWER CORD

NOTE:  
PLUG IS NOT SUITABLE AS A DISCONNECT. USER MUST SUPPLY A SUITABLE DISCONNECT.

VOLTAGE-120VAC  
14 AMPS  
1 HP SINGLE PHASE/50/60 Hz.  
20 AMP BRANCH CIRCUIT PROTECTION TO BE PROVIDED BY OTHERS DURING FIELD INSTALLATION.