



PLUGS ARE NOT SUITABLE AS DICONNECTS USER MUST SUPPLY SUITABLE DICONNECTS.

VOLTAGE-120VAC
 14 AMPS 1 HP
 SINGLE PHASE 50%
 Hz.
 20 AMP BRANCH
 CIRCUIT PROTECTION
 TO BE PROVIDED BY
 OTHERS DURING FIELD
 INSTALLTION FOR
 EACH CIRCUIT.

J:\AutoCAD\CAD 2016\SYSTEMS-151-DS STATION TYPEII 6INCH DOWN-SEND.dwg, 12/9/2016 10:24:10 AM

TOLERANCES ±1/32" FRACTIONAL DIMENSIONS
 TOLERANCES ±.005" DECIMAL DIMENSIONS
 UNLESS OTHERWISE SPECIFIED

INFORMATION CONTAINED HEREIN IS
 PROPRIETARY TO EAGLE PNEUMATIC, INC.
 ALL RIGHTS RESERVED

TITLE:
 STATION, TYPE II
 6 INCH DOWN-SEND

MATERIAL:

FINISH:

REV. 4-12/29/04
 1.11/18/97
 2.-3/13/03
 3.-8/5/03

DRAWN: JAC
 CADFILE\ A29

DATE: 11/18/97



EAGLE
 PNEUMATIC, INC.
 (863)644-4870

DRAWING NO.
 S-151-DS

APPROVED:

ISSUE
 4